

CST

**WHERE PASSION
MEETS THE GROUND**

CATALOGUE 2021

This version is applied for TBL Ha Noi Co., Ltd only

A large white semi-truck with a long, dark-colored trailer is parked in a lot. The truck is viewed from a low angle, emphasizing its size. The background shows a sunset sky with soft, orange and yellow clouds. The truck's headlights are on, and the overall scene is bathed in the warm light of the setting sun.

ROAD TRACTOR

www.cstires.com

INDEX

Other Products - Applied for only road tractors, trailers or semi-trailers

SIZE	Pattern	PR	Load	Speed Index	O.D.	S.W.	Max. Press(kPa/psi)	Max. Load (kg/lbs)	Rim
215/75 R17.5	CR105	16	128/126	M	774	213	(S) 750/110 (D) 750/110	(S) 1800/3970 (D) 1700/3750	6.00
215/75 R17.5	CR285	16	135/133	J	774	213	(S) 850/123 (D) 850/123	(S) 2180/4805 (D) 2060/4540	6.00
235/75 R17.5	CR105	16	132/129	M	803	234	(S) 830/120 (D) 830/120	(S) 2000/4410 (D) 1850/4080	6.75
235/75 R17.5	CR285	18	143/141	J	807	236	(S) 875/125 (D) 875/125	(S) 2725/6005 (D) 2575/5675	6.75
9.5 R17.5	CR836	16	143/141	K	844	233	(S) 875/127 (D) 875/127	(S) 2725/6005 (D) 2575/5675	6.75
9.5R17.5	CR969	18	143/141	J	844	238	(S) 875/127 (D)875/127	(S) 2725/6005 (D) 2575/5675	6.75
245/70 R19.5	CR277	16	135/133	M	840	250	(S) 830/120 (D) 830/120	(S) 2180/4805(D) 2060/4540	7.50
245/70 R19.5	CR105+	18	141/140	M	844	244	(S) 850/123 (D) 850/123	(S) 2575/5675 (D) 2500/5510	7.50
245/70 R19.5	CR287	18	141/140	K	844	246	(S)850/123 (D)850/123	(S) 2575/5675 (D) 2500/5510	7.50
265/70 R19.5	CR969	18	143/141	J	874	262	(S) 850/123 (D) 850/123	(S) 2725/6005 (D) 2575/5675	7.50
265/70 R19.5	CR105	18	143/141	J	875	256	(S) 850/123 (D) 850/123	(S) 2725/6005(D) 2575/5675	7.50
265/70 R19.5	CR285	16	139/136	M	875	263	(S) 830/120 (D) 830/120	(S) 2430/5355 (D) 2240/4940	7.50
255/70 R22.5	CR105+	16	140/137	M	930	250	(S) 830/120 (D) 830/120	(S) 2500/5510 (D) 2300/5070	7.50
255/70 R22.5	CR180	16	140/137	M	930	250	(S) 830/120 (D) 830/120	(S) 2500/5510 (D) 2300/5070	7.50
10 R22.5	CR277	16	144/142	M	1011	260	(S) 900/130 (D) 900/130	(S) 2800/6175 (D) 2650/5840	7.50
10 R22.5	CR105+	16	144/142	M	1021	256	(S) 900/130 (D) 900/130	(S) 2800/6175 (D) 2650/5840	7.50
10.00 R20	CR285	16	147/143	K	1052	278	(S) 800/116 (D) 800/116	(S) 3075/6780 (D) 2725/6005	7.50
10.00 R20	CR939+	16	146/143	K	1057	278	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50
10.00 R20	CR969+	16	146/143	K	1059	278	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50
10.00 R20	CR969K	18	149/146	K	1059	278	(S) 930/135 (D) 930/135	(S) 3250/7160 (D) 3000/6610	7.50
10.00 R20	CR989K	18	149/146	K	1059	278	(S) 930/135 (D) 930/135	(S) 3250/7160 (D) 3000/6610	7.50
10.00 R20	CR979	16	146/143	K	1063	282	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50
10.00R20	CR817	16	146/143	K	1065	278	(S) 830/120 (D) 830/120	(S) 3000/6615(D) 2725/6005	7.50
10.00 R20	CR327	16	146/143	K	1068	280	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50
11.00 R20	CR285	18	152/149	K	1085	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00
11.00 R20	CR989+	18	152/149	K	1086	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00
11.00 R20	CR989K	18	152/149	K	1086	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00
11.00 R20	CR939+	18	152/149	K	1087	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00
11.00 R20	CR969+	18	152/149	K	1089	295	(S) 930/135 (D) 930/135	(S)3550/7830 (D) 3250/7160	8.00
11.00 R20	CR307	16	150/147	F	1093	292	(S) 830/120 (D) 830/120	(S) 3350/7390 (D) 3075/6780	8.00
11.00 R20	CR327	18	152/149	J	1094	297	(S) 930/135 (D) 930/135	(S) 3550/7825 (D) 3250/7165	8.00
275/70 R22.5	CR105	18	148/145	J	966	277	(S) 900/130 (D) 900/130	(S) 3150/6940 (D) 2900/6395	8.25
275/70 R22.5	CR105	18	152/148	F	966	277	(S) 900/130 (D) 900/130	(S) 3150/6940 (D) 2900/6395	8.25
275/70 R22.5	CR285	18	148/145	L	967	280	(S) 900/130 (D) 900/130	(S) 3150/6940 (D) 2900/6395	8.25
275/80 R22.5	CR285	16	149/146	M	1023	279	(S) 850/123 (D) 850/123	(S) 3250/7165 (D) 3000/6615	8.25
11 R22.5	CR298	16	148/145	M	1052	280	(S) 850/123 (D) 850/123	(S) 3150/6940 (D) 2900/6395	8.25
11R22.5	CR189+	16	148/145	M	1052	280	(S) 850/123 (D) 850/123	(S) 3150/6945(D) 2900/6395	8.25
11 R22.5	CR285	16	148/145	M	1052	283	(S) 850/123 (D) 850/123	(S) 3150/6945 (D) 2900/6395	8.25
11 R22.5	CR105	18	152/148	J	1058	277	(S) 830/120 (D) 830/120	(S) 3550/7830 (D) 3150/6940	8.25
11 R22.5	CR969	16	148/145	K	1058	278	(S) 850/123 (D) 850/123	(S) 3150/6945 (D) 2900/6395	8.25
12.00 R20	CR939+	18	154/151	K	1121	315	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	8.50
12.00 R20	CR189	20	156/153	K	1121	316	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50
12.00 R20	CR969+	20	156/153	K	1124	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50

INDEX

Other Products - Applied for only road tractors, trailers or semi-trailers

SIZE	Pattern	PR	Load	Speed Index	O.D.	S.W.	Max. Press(kPa/psi)	Max. Load (kg/lbs)	Rim
12.00 R20	CR989+	20	156/153	K	1124	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50
12.00 R20	CR989K	20	156/153	K	1124	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50
12.00 R20	CR387	20	156/153	K	1125	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50
12.00 R20	CR307	18	154/151	F	1130	315	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	8.50
12.00 R20	CR337	20	156/153	F	1130	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50
12.00 R20	CR327	20	156/153	J	1131	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50
12.00 R24	CR307	20	160/156	F	1246	314	(S)850/130 (D)850/130	(S) 4500/9920 (D) 4000/8820	8.50
295/60 R22.5	CR269+	18	150/147	L	924	289	(S) 900/130 (D) 900/130	(S) 3350/7390 (D) 3075/6780	9.00
315/70 R22.5	CR269	20	154/151	L	1015	310	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00
295/80 R22.5	CR269+	18	152/149	M	1052	306	(S) 900/130 (D)900/130	(S) 3550/7830 (D) 3250/7160	9.00
295/80 R22.5	CR808	18	152/148	L	1053	305	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3150/6940	9.00
295/80 R22.5	CR298	18	152/148	M	1053	306	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3150/6940	9.00
295/80 R22.5	CR285	16	152/148	M	1053	307	(S) 850/123 (D) 850/123	(S) 3550/7825 (D) 3150/6945	9.00
295/80 R22.5	CR651	18	152/149	M	1053	308	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3250/7160	9.00
295/80 R22.5	CR105+	18	152/149	J	1054	304	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00
295/80 R22.5	CR817	16	152/148	M	1060	306	(S) 850/123 (D) 850/123	(S) 3550/7825 (D) 3150/6945	9.00
295/80 R22.5	CR969 SR	16	152/148	M	1060	306	(S) 850/123 (D) 850/123	(S) 3550/7825 (D) 3150/6945	9.00
315/80 R22.5	CR277	18	154/150	M	1078	318	(S) 825/120 (D) 825/120	(S) 3750/8270(D) 3350/7390	9.00
315/80 R22.5	CR939+	20	157/154	L	1081	314	(S) 900/130 (D) 900/130	(S) 4125/9090 (D) 3750/8270	9.00
315/80 R22.5	CR269	18	156/150	M	1082	315	(S) 850/123 (D) 850/123	(S) 4000/8820 (D) 3350/7390	9.00
315/80 R22.5	CR298	20	157/154	L	1082	316	(S) 900/130 (D) 900/130	(S) 4125/9090 (D) 3750/8270	9.00
12R22.5	CR387 SR	18	154/151	K	1084	296	(S) 930/135 (D) 930/135	(S) 3750/8270(D) 3450/7610	9.00
315/80R22.5	CR808	18	154/150	L	1084	315	(S) 825/120 (D) 825/120	(S) 3750/8270(D) 3350/7390	9.00
12 R22.5	CR285	16	152/148	L	1085	298	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3150/6940	9.00
12 R22.5	CR285SR	20	154/151	L	1085	298	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00
12 R22.5	CR269+	18	152/149	L	1086	305	(S) 930/135 (D)930/135	(S) 3550/7830 (D) 3250/7160	9.00
12 R22.5	CR600	18	152/149	L	1086	305	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00
12 R22.5	CR700	18	152/149	L	1086	305	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00
12 R22.5	CR298 P	18	152/148	L	1088	299	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3150/6940	9.00
12 R22.5	CR939+SR	20	154/151	K	1090	295	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00
12 R22.5	CR969+	16	150/147	K	1090	297	(S) 830/120 (D) 830/120	(S) 3350/7390 (D) 3075/6780	9.00
315/80 R22.5	CR826	18	154/151	M	1093	316	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	9.00
315/60 R22.5	CR269+	20	153/150	L	947	317	(S) 900/130 (D) 900/130	(S) 3650/8050 (D) 3350/7390	9.75
385/65 R22.5	CR297	20	160	J	1073	377	(S) 900/130	(S) 4500/9920	11.75

Below are Cheng Shin Brand

Applied for only road tractors, trailers or semi-trailers

SIZE	Pattern	PR	Load	Speed Index	O.D.	S.W.	Max. Press(kPa/psi)	Max. Load (kg/lbs)	Rim
11.00 R20	CR969+	18	152/149	K	1089	295	(S) 930/135 (D) 930/135	(S)3550/7830 (D) 3250/7160	8.00
12.00 R20	CR387	20	156/153	K	1125	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50
12R22.5	CR387 SR	18	154/151	K	1084	296	(S) 930/135 (D) 930/135	(S) 3750/8270(D) 3450/7610	9.00
425/65 R22.5	CR297	20	164	K	1126	413	(S) 830/120	(S) 5000/11000	12.25