

CST[®]

**WHERE PASSION
MEETS THE GROUND**

CATALOGUE

This version is applied for TBL Ha Noi Co., Ltd; Vietnam only



With special design and compound for only use of
trailer or semi-trailer
All these tyres in these catalogue cannot be
used for lorries truck and buses.

CR285/CR285 HD/CR285II/CR285U CR285P/CR285+/CR285 SR



- Designed for only trailer or semi-trailer
- Better performance for stone and mud resistance
- Low rolling resistance and fuel saving
- Special tread structure offers long abrasion resistance

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



	Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
	10R22.5 144/142M	16	1018	260	(S) 900/130 (D) 900/130	(S) 2800/6175 (D) 2650/5840	7.50	TL
	10.00R20 147/143K	16	1052	278	(S) 800/116 (D) 800/116	(S) 3075/6780 (D) 2725/6005	7.50	TT
	10.00 R20 149/146K	18	1052	282	(S) 930/135 (D) 930/135	(S) 3250/7160 (D) 3000/6610	7.50	TT
	11.00R20 152/149K	18	1081	285	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00	TT
	11R22.5 148/145M	16	1052	283	(S) 850/123 (D) 850/123	(S) 3150/6945 (D) 2900/6395	8.25	TL
	11R22.5 149/146M	18	1048	282	(S) 930/135 (D) 930/135	(S) 3250/7160 (D) 3000/6610	8.25	TL
	12R22.5 152/148L	16	1085	298	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3150/6940	9.00	TL
	12R22.5 152/149L	18	1083	296	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL
	12R22.5 154/151L	20	1088	297	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL
	13R22.5 156/153L	20	1121	319	(S) 930/135 (D) 930/135	(S) 4000/8820 (D) 3650/8050	9.75	TL
	205/75R17.5 125/123M	16	760	203	(S) 830/120 (D) 830/120	(S) 1650/3640 (D) 1550/3415	6.00	TL
	245/70R17.5 143/141J	18	790	248	(S) 875/128 (D) 875/128	(S) 2725/6005 (D) 2575/5675	7.50	TL
	245/70R19.5 141/140K	18	844	247	(S) 850/123 (D) 850/123	(S) 2575/5675 (D) 2500/5510	7.50	TL
	215/75R17.5 126/124M	12	774	213	(S) 700/102 (D) 700/102	(S) 1700/3750 (D) 1600/3530	6.00	TL
	215/75R17.5 135/133J	16	774	213	(S) 850/123 (D) 850/123	(S) 2180/4805 (D) 2060/4540	6.00	TL
	235/75R17.5 143/141J	18	807	236	(S) 875/127 (D) 875/127	(S) 2725/6005 (D) 2575/5675	6.75	TL
	265/70R19.5 139/136M	16	875	263	(S) 830/120 (D) 830/120	(S) 2430/5355 (D) 2240/4940	7.50	TL
	265/70R19.5 146/144L	20	875	263	(S) 900/130 (D) 900/130	(S) 3000/6610 (D) 2800/6175	7.50	TL
	285/70R19.5 150/148J	18	894	285	(S) 900/130 (D) 900/130	(S) 2900/6395 (D) 2650/5840	8.25	TL
	275/70R22.5 148/145L	18	967	277	(S) 900/130 (D) 900/130	(S) 3150/6940 (D) 2900/6395	8.25	TL
	275/80R22.5 149/146M	18	1023	279	(S) 900/130 (D) 900/130	(S) 3250/7160 (D) 3000/6610	8.25	TL
	275/80R22.5 149/146M	18	1018	280	(S) 900/130 (D) 900/130	(S) 3250/7160 (D) 3000/6610	8.25	TL
	295/80R22.5 152/148M	16	1053	307	(S) 850/123 (D) 850/123	(S) 3550/7825 (D) 3150/6945	9.00	TL

CR297

- Designed for only trailer or semi-trailer with standard load, long distance on good roads conditions
- Cross-ladder pattern design with good stone rejection performance
- Low heat generation rubber and special carcass structure extend tire life
- Durable carcass offers a long and recyclable tread life



**This product cannot be used for lorries truck and buses.*

RECOMMENDED



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
385/65R22.5 160K	20	1073	378	(S) 900/130	(S) 4500/9920	11.75	TL
425/65R22.5 164K	20	1136	412	(S) 830/120	(S) 5000/11000	12.25	TL

CST

CR298/CR298AP/CR298A CR298P

- Designed for only trailer or semi-trailer for middle to long distances
- Special tread structure improves stone rejection and prevents uneven wearing
- A flat, wide tread and special tread compound achieve a long tread life



**This product cannot be used for lorries truck and buses.*

RECOMMENDED



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
11R22.5 146/143M	16	1052	280	(S) 830/120 (D) 830/120	(S) 3000/6610 (D) 2725/6005	8.25	TL
12R22.5 152/149L	18	1084	296	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL
295/80R22.5 152/149M	18	1053	307	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL
315/80R22.5 157/154L	20	1082	316	(S) 900/130 (D) 900/130	(S) 4125/9090 (D) 3750/8270	9.00	TL

CST

CR269 CR269+

- Designed for middle and short distances at higher speeds on good road conditions, suitable for only trailer or semi-trailer
- A flat, wide tread and special tread structure provides a long tread life and improves stone rejection and prevents uneven wear



**This product cannot be used for lorries truck and buses.*

RECOMMENDED



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL	
12R22.5 152/149L	18	1086	305	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL	
295/80R22.5 152/149M	18	1052	306	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL	
295/60R22.5 150/147L	18	924	289	(S) 900/130 (D) 900/130	(S) 3350/7390 (D) 3075/6780	9.00	TL	NEW
315/60R22.5 153/150L	20	947	317	(S) 900/130 (D) 900/130	(S) 3650/8050 (D) 3350/7390	9.75	TL	NEW
315/70R22.5 154/151L	20	1015	310	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL	NEW
315/80R22.5 156/150M	18	1082	315	(S) 850/123 (D) 850/123	(S) 4000/8820 (D) 3350/7390	9.00	TL	NEW

CR817

- Designed for highway and middle-long distance, especially only trailer or semi-trailer
- Extra-wide block and lug depth tread pattern design resists abrasion
- Advanced bead design provides excellent load capability



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
10.00R20 146/143K	16	1065	278	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50	TT
295/80R22.5 152/148M	16	1060	306	(S) 850/123 (D) 850/123	(S) 3550/7825 (D) 3150/6945	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR808

- Designed for only trailer or semi-trailer middle and long distance and for high loads on a variety of road conditions
- Optimised block pattern improves anti-wearing ability
- Special tread structure improves stone rejection and offers excellent heat generation performance
- Durable carcass achieves a long and recyclable tread life



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
295/80R22.5 152/148L	18	1053	305	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3150/6940	9.00	TL
315/80R22.5 154/150L	18	1084	315	(S) 825/120 (D) 825/120	(S) 3750/8270 (D) 3350/7390	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CST

CR189/CR189II/CR189A CR189+



- Providing comfortable, silent, straight ahead performance
- Advanced tread compound achieves low heat generation and provides high durability
- For only trailer or semi-trailer on-road and highway use
- Strong anti-wear shoulder extends tire mileage

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
11R22.5* 148/145M	16	1047	282	(S) 850/123 (D) 850/123	(S) 3150/6945 (D) 2900/6395	8.25	TL
12.00R20 156/153K	20	1117	313	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT

*11R22.5 belongs to standard load, which is with upgraded pattern CR189+ to achieve better anti-wearing ability

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR939+/CR939+SR



- Designed for only trailer or semi-trailer for on road and high speed use
- Special pattern and strong shoulder design prevents uneven wear
- Four high tensile belts provide a superior strength casing to resist cracking and puncture
- A flat, wide tread with special compound delivers long tread life

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
10.00R20 146/143K	16	1057	276	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50	TT
11.00R20 152/149K	18	1086	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00	TT
12.00R20 154/151K	18	1121	315	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	8.50	TT
12.00R20 156/153K	20	1121	315	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	8.50	TT
12R22.5 154/151K	20	1084	296	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL
13R22.5 156/153L	20	1127	321	(S) 930/135 (D) 930/135	(S) 4000/8820 (D) 3650/8050	9.75	TL
315/80R22.5 157/154L	20	1078	314	(S) 900/130 (D) 900/130	(S) 4125/9090 (D) 3750/8270	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR969/CR969II/CR969+SR/CR969SR

CR969+/CR969K/CA901/CA901UT

CA969/CA969UT



- For only trailer or semi-trailer
- Designed for heavy load capability
- Special bead area structure provides excellent load stability
- Deep tread aids in resistance to abrasions
- High durability and excellent retreadability
- Special compound offers anti-cutting ability

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
265/70 R19.5 143/141J	18	874	262	(S) 850/123 (D) 850/123	(S) 2725/6005 (D) 2575/5675	7.50	TL
10.00R20 146/143K	16	1059	276	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50	TT
10.00R20 149/146K	18	1059	276	(S) 930/135 (D) 930/135	(S) 3250/7165 (D) 3000/6615	7.50	TT
11.00R20 152/149K	18	1089	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00	TT
12.00R20 156/153K	20	1124	313	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT
12.00R24 160/156K	20	1224	312	(S) 850/123 (D) 850/123	(S) 4500/9920 (D) 4000/8820	8.50	TT
11R22.5 148/145K	16	1058	278	(S) 850/123 (D) 850/123	(S) 3150/6945 (D) 2900/6395	8.25	TL
12R22.5 150/147K	16	1090	297	(S) 830/120 (D) 830/120	(S) 3350/7390 (D) 3075/6780	9.00	TL
12R22.5 154/151K	20	1085	296	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL
13R22.5 156/153K	20	1120	312	(S) 930/135 (D) 930/135	(S) 4000/8820 (D) 3650/8050	9.75	TL
295/80R22.5 152/148M	16	1060	306	(S) 850/123 (D) 850/123	(S) 3550/7825 (D) 3150/6945	9.00	TL

*This product cannot be used for lorries truck and buses.

RECOMMENDED



CR387/CR387K/CR387SR

- Designed for only trailer or semi-trailer
- Lug tread pattern and block shoulder pattern provides excellent grip performance
- Special tread structure improves load capability
- Special tread compound aids in anti-wearing ability



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
10.00R20 149/146K	18	1056	280	(S) 930/135 (D) 930/135	(S) 3250/7160 (D) 3000/6610	7.50	TT
11.00R20 152/149K	18	1088	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00	TT
12.00R20 156/153K	20	1120	313	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT
12R22.5 154/151K	18	1084	296	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR327/CR327K/CR328K CR328/CL501/CL501UT

- Designed for only trailer or semi-trailer for short distances and low-speed use
- Special tread compound aids in resistance to cutting and tearing
- Special tire structure provides superior load capacity
- Durable carcass achieves a long and recyclable tread life



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
10.00R20 146/143K	16	1068	280	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50	TT
10.00 R20 149/146K	18	1068	280	(S) 930/135 (D) 930/135	(S) 3250/7160 (D) 3000/6610	7.50	TT
11.00R20 152/149K	18	1094	297	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00	TT
12.00R20 156/153J	20	1130	317	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT
12.00R20 156/153K	20	1126	313	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR307

- Designed for only trailer or semi-trailer use in short distances and low speed
- Extra-deep and block pattern delivers a long tread life
- Extra block pattern prevents cutting and tearing



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
11.00R20 150/147F	16	1093	292	(S) 830/120 (D) 830/120	(S) 3350/7390 (D) 3075/6780	8.00	TT
12.00R20 154/151F	18	1130	315	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	8.50	TT
12.00R24 160/156F	20	1247	313	(S) 850/130 (D) 850/130	(S) 4500/9920 (D) 4000/8820	8.50	TT

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR337

- Designed for only trailer or semi-trailer use in short distances and low speed
- Special tread compound aids resistance to cutting and tears.
- Durable carcass achieves a long and recyclable tread life



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12.00R20 156/153F	20	1130	313	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT
11.00R20 152/149F	18	1090	282	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00	TT

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR600/CR600A

Designed for only trailer or semi-trailer highway use at higher speeds for middle to long distances.

Tread structure improves stone rejection and prevents uneven wear.

Flat, wide tread with special compound delivers long life.



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/ TL
12R22.5 152/149L	18	1086	305	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL
295/60R22.5 150/147L	18	926	288	(S) 900/130 (D) 900/130	(S) 3350/7390 (D) 3075/6780	9.00	TL
295/60R22.5 150/147K	18	926	288	(S) 900/130 (D) 900/130	(S) 3350/7390 (D) 3075/6780	9.00	TL
295/80R22.5 152/149M	18	1049	296	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL
315/60R22.5 153/150L	20	947	317	(S) 900/130 (D) 900/130	(S) 3650/8050 (D) 3350/7390	9.75	TL
315/70R22.5 154/151L	20	1013	312	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL
315/80R22.5 157/154L	20	1082	315	(S) 900/130 (D) 900/130	(S) 4125/9090 (D) 3750/8270	9.00	TL
275/80R22.5 149/146M	18	1018	283	(S) 900/130 (D) 900/130	(S) 3250/7160 (D) 3000/6610	8.25	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



MULTI BUX

Designed for only trailer or semi-trailer highway use at higher speeds for middle to long distances.

Tread structure improves stone rejection and prevents uneven wear.

Flat, wide tread with special compound delivers long life.



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1086	305	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL
295/80R22.5 152/149L	18	1050	306	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR989+/CR989K

- For only trailer or semi-trailer on good road
- Extraordinary tread pattern for better endurance
- Specific tread structure offers lower heat generation
- Specific tread compound achieves a long and recycle tread life



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
10.00R20 146/143K	16	1059	279	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	7.50	TT
10.00R20 149/146K	18	1059	277	(S) 930/135 (D) 930/135	(S) 3250/7160 (D) 3000/6610	7.50	TT
11.00R20 152/149K	18	1085	294	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	8.00	TT
12.00R20 156/153K	20	1124	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT

**This product cannot be used for lorries truck and buses.*

RECOMMENDED





**This product cannot be used for lorries truck and buses.*

RECOMMENDED



K SERIES Super heavy load suitable use for only trailer or semi-trailer at port

Size	Pattern	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12.00R20 156/153K	CR390K	20	1125	315	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT

CST

CR105 CR105+

- Designed for only trailer or semi-trailer
- A flat, wide tread design delivers safety and comfort
- Special tread compound lowers heat generation and provides better durability
- Three straight-grooved design enlarges the pattern blocks and increase pattern rigidity
- Narrow-bottom groove design prevents stone penetration
- Durable carcass offers a long and recyclable tread life



**This product cannot be used for lorries truck and buses.*

RECOMMENDED



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
10R22.5 144/142M	16	1021	256	(S) 900/130 (D) 900/130	(S) 2800/6175 (D) 2650/5840	7.50	TL
11R22.5 152/148J	18	1056	277	(S) 830/120 (D) 830/120	(S) 3550/7830 (D) 3150/6940	8.25	TL
215/75R17.5 128/126M	16	774	210	(S) 750/110 (D) 750/110	(S) 1800/3970 (D) 1700/3750	6.00	TL
235/75R17.5 132/129M	16	803	234	(S) 830/120 (D) 830/120	(S) 2000/4410 (D) 1850/4080	6.75	TL
245/70R19.5 141/140M	18	844	244	(S) 850/123 (D) 850/123	(S) 2575/5675 (D) 2500/5510	7.50	TL
255/70R22.5 140/137M	16	936	250	(S) 830/120 (D) 830/120	(S) 2500/5510 (D) 2300/5070	7.50	TL
275/70R22.5 148/145J	18	968	284	(S) 900/130 (D) 900/130	(S) 3150/6940 (D) 2900/6395	8.25	TL
275/70R22.5 152/148J	18	968	284	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3150/6940	8.25	TL
295/80R22.5 152/149J	18	1053	302	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL
265/70R19.5 143/141J	18	875	256	(S) 850/123 (D) 850/123	(S) 2725/6005 (D) 2575/5675	7.50	TL

CST

CR277 CR287



- Designed for only trailer or semi-trailer with standard load, long distance on good roads conditions
- Low heat-generation design for highway use provides comfort and safety
- Strong anti-wear shoulder extends tire mileage

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
245/70R19.5 135/133M	16	840	250	(S) 830/120 (D) 830/120	(S) 2180/4805 (D) 2060/4540	7.50	TL
10R22.5 144/142M	16	1011	260	(S) 900/130 (D) 900/130	(S) 2800/6175 (D) 2650/5840	7.50	TL
315/80R22.5 154/150M	18	1078	318	(S) 825/120 (D) 825/120	(S) 3750/8270 (D) 3350/7390	9.00	TL
245/70R19.5 141/140K	18	844	246	(S) 850/123 (D) 850/123	(S) 2575/5675 (D) 2500/5510	7.50	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED





CR700/CR701A/CR701

Designed for only trailer or semi-trailer highway use at higher speeds for middle to long distances.

Tread structure improves stone rejection and prevents uneven wear.

Flat, wide tread with special compound delivers long life.



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1086	305	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CST

CR826 CR826 P



- Designed for only trailer or semi-trailer middle and long distance and for high loads on a variety of road conditions
- Optimised block pattern improves anti-wearing ability
- Special tread structure improves stone rejection and offers excellent heat generation performance
- Durable carcass achieves a long and recyclable tread life

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1095	302	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL
315/80R22.5 154/151M	18	1093	316	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR651

Designed for only trailer or semi-trailer for long distance at higher speeds on highways

Four jagged-line circumferencial grooves combined with a strengthened shoulder structure offer strong resistance to uneven wear

Groove design provides efficient stone ejection



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/ TL
295/80R22.5 152/149M	18	1053	307	(S) 850/123 (D) 850/123	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR295II



Designed for only trailer or semi-trailer middle to long distances on freeways or highways.

Optimised tire structure delivers a more cost-effective performance

Shallow angled grooves on the tread enhance the rigidity of the pattern block for extra stability

'City wall' groove wall design offers excellent stone ejection

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1082	301	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR170

For only trailer or semi-trailer
large cargo, mid-long distance

Wide tread with deep grooves offers an extended tire lifespan

Special tire structure designed to provide superior durability

Low flat ratio design specifically ideal for heavy cargo
transportation

Staggered notch design of the groove walls promotes
efficient stone and debris ejection



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/ TL
205/65R17.5 129/127K	18	710	198	(S) 900/130 (D) 900/130	(S) 1850/4080 (D) 1750/3860	6.00	TL
245/70R17.5 143/141J	18	790	252	(S) 875/128 (D) 875/128	(S) 2725/6005 (D) 2575/5675	7.50	TL
215/75R17.5 135/133J	16	772	212	(S) 850/123 (D) 850/123	(S) 2180/4805 (D) 2060/4540	6.00	TL
235/75R17.5 143/141J	16	795	238	(S) 875/127 (D) 875/127	(S) 2725/6005 (D) 2575/5675	6.75	TL
245/70R19.5 141/140J	18	843	245	(S) 850/123 (D) 850/123	(S) 2575/5675 (D) 2500/5510	7.50	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CD817

Designed for only trailer or semi-trailer
for long distances at higher speeds

Durable carcass provides a long and recyclable tread life

Low-heat-generating compound offers safety and comfort

Staggered half-step groove wall design offers efficient
stone ejection



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/ TL
295/80R22.5 152/149M	18	1053	307	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL
11R22.5 146/143L	16	1060	284	(S) 830/120 (D) 830/120	(S) 3000/6615 (D) 2725/6005	8.25	TL
315/80R22.5 154/151L	18	1090	318	(S) 830/120 (D) 830/120	(S) 3750/8270 (D) 3450/7610	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR836/CR866



Designed for only trailer or semi-trailer
for middle to long distance at higher speeds

Connecting bridge between blocks increases pattern rigidity
and avoids uneven wearing

Narrow tread and deep groove helps improve fuel economy

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/ TL
12R22.5 152/149L	18	1086	290	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CL301UT

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12.00R20 156/153K	20	1120	313	(S) 900/130 (D) 900/130	(S) 4000/8820 (D) 3650/8050	8.50	TT

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR161+

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1076	300	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR166T/CA179SR

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1079	295	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL
12R22.5 154/151L	20	1079	295	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CA162



Designed for only trailer or semi-trailer

Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1075	303	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CA172

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1075	296	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CA185A

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1082	300	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CA186A

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1084	296	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CD800

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
12R22.5 152/149L	18	1089	296	(S) 930/135 (D) 930/135	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CR180

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
255/70R22.5 143/140J	18	930	249	(S) 900/130 (D) 900/130	(S) 2725/6005 (D) 2500/5510	7.50	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CA290EV

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
275/70R22.5 152/148J	18	968	284	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3150/6940	8.25	TL
305/70R22.5 153/150J	20	1002	304	(S) 900/130 (D) 900/130	(S) 3650/8050 (D) 3350/7390	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



SCA10

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
315/70R22.5 154/151L	20	1009	322	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL
295/80R22.5 152/149M	18	1048	297	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



SCD81

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
315/70R22.5 154/151L	20	1012	322	(S) 930/135 (D) 930/135	(S) 3750/8270 (D) 3450/7610	9.00	TL
295/80R22.5 152/149M	18	1051	297	(S) 900/130 (D) 900/130	(S) 3550/7830 (D) 3250/7160	9.00	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



CA970

Designed for only trailer or semi-trailer



Size	Ply rating	Overall diam. (mm)	Section width (mm)	Max press. (kpa/psi)	Max load (kg/lbs)	Meas. rim width (in)	Type TT/TL
275/80R22.5 149/146M	18	1017	283	(S) 900/130 (D) 900/130	(S) 3250/7160 (D) 3000/6610	8.25	TL

**This product cannot be used for lorries truck and buses.*

RECOMMENDED



The CST logo is displayed in a bold, white, italicized sans-serif font. The letters 'C' and 'S' are connected, and the 'T' has a distinctive slanted top. A small registered trademark symbol (®) is located to the right of the 'T'.

CST®

**WHERE PASSION
MEETS THE GROUND**

CATALOGUE

